

Multi - LNG White

Aplicatii

Multi-LNG White este special construit pentru transfer lichide refrigerate pana la -196 grade C cum ar fi LNG in calea ferata, vagoane cisterna, zone industriale, descarcare nave la tarm.

Certificari

Furtunurile Multi-LNG White sunt produse si testate in conformitate cu standarde internationale cum ar fi EN 13766:2003 & IMO IGC.

Constructie

Spirala interioara	Otel inox 316
Tub	Foi si folii din poliester
Invelis exterior	Poliamida
Spirala exterioara	Otel inox 316

Proprietati fizice

Intindere maxima	10% din presiunea de test
Rezistenta electrica	<10 Ohm p/lungime
Rasucire maxima	10 grade p/m
Presiune spargere minima	5x presiune lucru (factor siguranta 5:1)
Debit maxim	la cerere
Rezistenta maxima la intindere	la cerere
Pierdere presiune	la cerere
Domeniu temperatura	intre -196 grade C pana la +50 grade C



Multi-LNG White, Cod 281039300

Diametru		Presiune lucru max.		Raza curbura		Greutate		Lungime maxima	
inches	mm	PSI	bar	inches	mm	lbs/Ft	Kg/m	Ft	m
1	28	150	10,5	5,9	150	0,6	0,9	65	20
1,5	40	150	10,5	7,9	200	1,1	1,6	100	30
2	50	150	10,5	7,9	200	1,6	2,4	100	30
2,5	65	150	10,5	7,9	200	2,1	3,2	100	30
3	80	150	10,5	9,8	250	3,3	4,9	100	30
4	100	150	10,5	19,6	500	6	9	100	30
6	150	150	10,5	25,9	660	8,4	12,6	100	30
8	200	150	10,5	35,8	910	13,5	20,1	100	30
10	250	150	10,5	98,4	2500	16	23,9	65	20
12	300	150	10,5	137,8	3500	24,1	36	59	18

